



 SOUTHERN LEYTE STATE UNIVERSITY	REQUEST FOR QUOTATION GOODS AND SERVICES
Office/Campus:	BARGO
Address/Contact Details:	San Roque, Sogod, Southern Leyte

Purchase Request No.

202602022

Date:

BIDDER:

May we request for quotation on materials enumerated hereunder. If you are interested and in a position to furnish the same, we shall be glad to have your best prices.

General Conditions of the Contract:

- All entries must be typewritten/handwritten.
- Bidders shall provide correct and accurate information required in this form.
- Any interlineations, erasures, or overwriting shall be valid only if they are signed or initialed by you or any of your duly authorized representative/s.
- Quotations exceeding the Approved Budget for the Contract shall be rejected.
- In case of tie among bidders, SLSU shall adopt and employ "draw lots" as the tiebreaking method to finally determine the single winning provider in accordance with GPPB Circular 06-2005.
- Award of contract shall be made in accordance with the Implementing Rules and Regulations of RA 9184 and RA 12009, whichever is applicable.
- All bidders shall be required to include the cost of all taxes, such as, but not limited to, value added tax (VAT), income tax, local taxes, and other fiscal levies and duties which shall be itemized in the bid form and reflected in the detailed estimates. Such bids, including said taxes, shall be the basis for bid evaluation and comparison. Moreover, applicable custom duties, as well as other costs of acquisition such as delivery/freight, insurance, and bank charges, must be incorporated in the bid.
- Liquidated damages equivalent to one-tenth of one percent (0.1%) of the value of the goods not delivered within the prescribed delivery period shall be imposed per day of delay. The Southern Leyte State University may terminate the contract once the cumulative amount of liquidated damages reaches ten percent (10%) of the amount of the contract, without prejudice to other courses of action and remedies open to it.
- Delivery period on specified date.
- Warranty shall be a period of **SIX (6) months** for supplies and materials, **ONE (1) Year** for the equipment, from the date of acceptance by Southern Leyte State University.
- Price validity shall be a period of THIRTY (30) calendar days.
- Valid PHILGEPS registration certificates and Mayor's/Business Permit** shall be attached upon submission of the quotation.
- Notarized Omnibus Sworn Statement** shall be attached upon submission of quotation for ABC amounting to Fifty Thousand Pesos (P50,000.00) and above, in accordance to Annex "H" Appendix A of RA 9184
- Income/Business Tax Return** shall be attached upon submission of quotation for ABC amounting to Five Hundred Thousand Pesos (P500,000.00) and above, in accordance to Annex "H" Appendix A of RA 9184

Item #	QTY.	UNIT	ITEM/DESCRIPTION	APPROVED BUDGET	UNIT COST	TOTAL COST
Enhancement of the Multi-Purpose Court Sound System (1 LOT)						
1	6	unit	15 inch 3-Way Speaker <ul style="list-style-type: none"> Powered three-way PA loudspeaker featuring a 15-inch woofer. It has a 2000-watt peak, 1000-watt RMS power rating, and a frequency range of 40\text{ Hz} - 20\text{ kHz} (\$-10\text{ dB}\$). The speaker also includes updated Image Control waveguides, a flared port design, and a low-noise, low-distortion gain staging design. It offers a maximum SPL of 136.1\text{ dB}\$ and dispersion of 90^\circ \times 50^\circ\$. It also features a color LCD screen for DSP control, including Automatic Feedback Suppression and system limiting. 			
2	1	unit	32 Channel Console Mixer <ul style="list-style-type: none"> 32-channel analog mixing console with built-in digital processing. It features 24 D-Pre microphone preamps, 32 line inputs, 6 auxiliary sends, and 2 effects sends. It also includes a Hybrid Channel section with 3 types of reverb and 16 effects, as well as features like auto-ducker and auto-leveler. The console allows for control via an iPhone or iPod touch using the MGP Editor app, and has USB connectivity for both playback and recording. 			
3	1	unit	8 Channel Input Power Conditioner <ul style="list-style-type: none"> Channels: 8 Input Sensor Type: ICP, Voltage Frequency Range ($\pm 5\%$, Gain ≥ 100): 0.1Hz to 1000 kHz Coupling: AC Input / Output Connectors: BNC Input Voltage: 100 to 240 VAC 			

4	2	unit	<p>Dual 12-inch Powered Monitor Speaker</p> <p>Dual 12-inch Powered Monitor Speaker</p> <ul style="list-style-type: none"> • Custom-designed 12-inch woofer • 2414H-1 compression driver • Redesigned high-frequency horn • Power: 1,300W Peak / 650W RMS • Frequency response: 50Hz - 20kHz(-10 dB); 60Hz - 20kHz (-3dB) • Max SPL: 127 dB • Dispersion: 100°H x 60°V • Audio I/Os: 2 XLR Combo, 1 XLR passthrough • Advanced dbx DSP: Automatic Feedback Suppression, ducking, 100ms speaker delay, parametric EQ • Built-in 3-channel digital mixer • Backlit color LCD screen provides easy access to functions • Universal JBL Pro Connect app control • Bluetooth 5.0 streaming and control • Durable polypropylene cabinet and metal grille • Two ergonomic handles simplify transport • Built-in pole mount and optional EON700 Universal Yoke Mount expand system configuration options • Stackable cabinets allow easy storage • Dimensions: 26.3 x 15 x 12.75 in (669 x 382 x 324 mm) (HxWxD) • Weight: 32 pounds (14.5 kg) • Shipping dimensions: 27.8 x 19.64 x 17.28 in (706 x 499 x 439 mm) (HxWxD) • Shipping weight: 40.1 pounds (18.2 kg) 			
5	1	box	Electrical Royal Cord Cable #12, 100meters			
6	1	box	Electrical Royal Cord Cable #14, 100meters			
7	1	piece	<p>Flight Case Heavy Duty</p> <ul style="list-style-type: none"> •Type: Removable Front and Rear Doors: Doors 70mm deep internally •Material: 9mm Black hexa board. Other colours available (add to basket to view) •Ext Dims: w527mm x d724mm x h910mm (Inc Castors) •Depth between rails 500mm (Rackstrip is recessed 27mm front and rear)Other depths available, see accessories •Rackstrip type: Double hole fitted front and rear. Rack nuts bolts and washers supplied •97mm Gap between inside of doors to front and rear of racks to allow for knobs, connectors cables etc. •Hardware: Heavy duty Penn Elcom Fittings •Castors: 4" Swivel Rubber Castors (2 x Braked) •Rack Space: 16u •Rack Tyne: Standard 			
8	1	item	<p>Labor, Installation, Integration, Engineering, Testing & Commissioning</p> <p>Labor, Installation, Integration, Engineering, Testing & Commissioning</p> <ul style="list-style-type: none"> • Equipment bracket and Speaker support. • Conduits & Roughing-ins: EMT for signal conduit, Electrical cables, Hardware & Installation materials. • Wires, Cables, Connectors & other peripherals: -Terminal patch, panel plates with chassis mount connector. PVC and signal conduit. <p>Hardware and installation materials, Wires, Signal, Control and Microphone cables, Installation devices.</p> <ul style="list-style-type: none"> • Labor & Installation: Cable pulling and Roughing-ins, Wiring and termination, Testing and commissioning 			
9	2	roll	<p>Microphone Cable</p> <ul style="list-style-type: none"> •Type: Audio Cable •Connector Type: XLR •Connection Type: Wired •Connector Gender: Male-Female •Interface: Audio •Signal Type: Audio •Compatible Devices: Microphone •Materials: PVC •Shielding: shielding •Conductor Material: pure copper •Jacket Material: PVC 			
10	10	piece	<p>PL Mono</p> <ul style="list-style-type: none"> • 1/4-inch Mono Phone Plug with nickel-plated contacts • Stylised Shell design • Robust diecast shell • Great solderability with increased solder area • Precision machined contacts • Flexible grommet cable protection • Standard type • Improved solderability 			

11	4	unit	<p>Single 18-inch Powered Subwoofer</p> <p>Single 18-inch Powered Subwoofer</p> <ul style="list-style-type: none"> • Professional, powered 18-inch subwoofer designed for live sound reinforcement. • It features a 2,000-watt peak (1,000-watt RMS) Class D amplifier, an 18mm birch cabinet with optimized bracing, and a flared port design to minimize air noise and distortion. • It offers a frequency response of 35 Hz - 92 kHz (±3 dB) and a maximum SPL of 134 dB. • It also includes a color LCD screen for DSP control, integration for system control 			
12	1	piece	Snake Cable 24 input with 4 return 50meters			
13	1	unit	<p>Speaker Management System</p> <ul style="list-style-type: none"> • Loudspeaker management system with two line inputs (XLR), one RTA mic input (XLR), and six line outputs (XLR). • It features 8-band parametric EQ, a compressor, and advanced feedback suppression. • It offers both wired (USB Type B) and wireless (Ethernet) control options. 			
14	2	piece	<p>Ultimate Microphone Stand w/Boom</p> <ul style="list-style-type: none"> •Height: 67.25" - 38.625" •Base Radius: 26.375" •Boom Length: 18.75" - 31.25" •Folded Dimensions: (H) 38.25" x (W) 3.5" •Mast Tube Diameter: .875" 			
15	2	unit	<p>Wired Dynamic Microphone</p> <ul style="list-style-type: none"> •with 10 meters microphone cable •Audio frequency bandwidth: 70 - 20000 Hz •Sensitivity: 2.6 mV/Pa •Electrical impedance: 600 Ohms •Recommended load impedance: 2000 Ohms •Polar Pattern: Supercardioid •Body: metal •Finish: dark stage blue 			
16	20	pair	<p>XLR Male and XLR Female</p> <ul style="list-style-type: none"> • 3 pole male / female XLR cable connector with integrated capacitive shield to shell connection to avoid RF-interference and LF-noise • 360° shield contact on female connector ensures best possible shielding and chassis contact • Avoid ground loops as there is no LF-shield connection to ground 			
TOTAL				₱1,326,225.74		
Payment Term			If payment for deposit, please provide bank details:			

Very truly yours,

PRICES IN THE ABOVE OFFER ARE
CERTIFIED TRUE AND CORRECT:

MARIE KHUL C. LANGUB
BAC Chairperson

Authorized Company
Representative

(Signature over Printed Name)

JELYNE L. LORA
Canvasser

Company Name _____

Address _____

Tel. Nos. _____

T. I. N. _____

IMPORTANT:

1. Prices must be written clearly.
2. If offering a substitute/equivalent, specify the brand and make.
3. RFQ should be sealed.

