SECTION VIII- BIDDING FORMS

l.	CHECKLIST OF DOCUMENTS	77 - 78
II.	SLSU BID FORM NO. 1 (TECHNICAL PROPOSALS)	79 - 89
III.	SLSU BID FORM NO. 2 (FINANCIAL PROPOSALS)	90 - 91
IV.	SAMPLE FORMS	. 92 - 107

CHECKLIST OF DOCUMENTS

ENVELOPE NO. 1 - FIRST COMPONENT -ELIGIBILITY AND TECHNICAL COMPO	NENT	
I. ELIGIBILITY DOCUMENTS under <u>ITB</u> Clause 12.1 (a)		
CLASS "A" DOCUMENTS		
a. Legal Eligibility Documents:		
(i). SEC/DTI Registration	[]
(ii). Valid & Current Mayor's Permit/ Municipal Licenses– 2017	[]
(iii) Valid Tax Clearance	[]
b. Technical Eligibility Documents:		
(iv)(a). The statement of all ongoing government and private contracts shall include all such contracts within the year 2015 to present, prior to the deadline for the submission and receipt of bids, including contracts awarded but not yet started, if any and (See attached Sample Form Nos. SF-GOOD-13a)	[]
(iv)(b). Statement identifying the bidder's single largest completed contract to be bid contracts within the year 2015 to present, except under conditions provided for in Sec. 23.5.1.3 of the IRR (as amended, GPPB Res. No. 16-2014). (See attached Sample Form Nos. SF-GOOD-13b):	[]
These statements shall include, for each contract, the following: (iv.1) Name and Location of the Contracts; (iv.2) Date of Contracts; (iv.3) Kind of goods sold; (iv.4) Amount of contract and value of Outstanding Contracts; (iv.5) Date of delivery of goods; and (iv.6) End-user's acceptance or official receipt(s) issued for the contract, if completed.		
c. Financial Eligibility Documents:		
(v) The Prospective bidder's audited Financial Statement for the year 2015, stamped "received" by the BIR or its duly accredited and authorized institutions showing, among others, the prospective bidder's total and current assets and liabilities	[]

(vi) The prospective bidder's computation for its Net Financial Contracting Capacity (NFCC) which must be at least equal to the ABC to be bid (See attached Sample Form Nos. SF-GOOD-14)	[]
CLASS "B" DOCUMENTS		
(vii) Valid joint venture agreement, in case of a joint venture.	Γ]
		-
II. TECHNICAL DOCUMENTS under ITB Clause No. 12.1 (b):		
(b.i) BID SECURITY (Please see table at Section III-BDS 18.1)	[]
(b.ii) TECHNICAL PROPOSAL		
SLSU BID FORM NO. 1	<u></u>]
(b.iii) OMNIBUS SWORN STATEMENT:	<u>[</u>]
The Omnibus Sworn Statement by the prospective bidder or its duly authorized		_
representative as to the following:	[]
(1) Name, address and designation of authorized representative(2) The signatory is the duly authorized representative of the prospective bidder, and		
granted full power and authority to do, execute and perform any and all acts		
necessary and/or to represent the prospective bidder in the bidding, with the duly		
notarized Secretary's Certificate attesting to such fact, if the prospective bidder is a		
corporation, partnership, cooperative, or joint venture;(See attached Sample Form		
Nos SF-GOOD-35/ SF-GOOD -36) (a) Authority of Signatory - Special Power of Attorney []		
(b) Authority of Signatory - Secretary's Certificate []		
(3) It is not "blacklisted" or barred from bidding by the GOP or any of its agencies,		
offices, corporations, or LGUs, including foreign government/foreign or international		
financing institution whose blacklisting rules have been recognized by the GPPB;		
(4) Each of the documents submitted in satisfaction of the bidding requirements is an authentic copy of the original, complete, and all statements and information		
provided therein are true and correct;		
(5) It is authorizing the Head of the Procuring Entity or his duly authorized		
representative/s to verify all the documents submitted;		
(6) Statement of compliance with the disclosure provision under Section 47 of RA 9184 (Disclosure of Relations) in relation to other provisions of R.A. 3019.		
(7) It complies with existing labor laws and standards.		
(8) It complies with the responsibilities of a prospective or eligible bidder provided		
in the PBDs, such as:		
a. Carefully examined all of the bidding documents;		
 b. Acknowledged all conditions, local or otherwise, affecting the implementation of the Contract; 		
c. Made an estimate of the facilities available and needed for the contract to be		
bid, if any, and;		
d. Inquired or secured Supplemental/Bid Bulletin(s) issued for the project.		
(9) It did not give or pay, directly or indirectly, any commission, amount, fee, or any		
form of consideration, pecuniary or otherwise, to any person or official, personnel or representative of the government in relation to any procurement project or		
activity.	·	
ENVELOPE NO. 2 - SECOND COMPONENT -FINANCIAL COMPONENT		

SLSU BID FORM NO. 2- Financial Proposal with undertaking	[:]

SLSU BID FORM NO. 1- TECHNICAL PROPOSAL

VALERIO B. CABALO, Ph.D.

Chair, Bids and Awards Committee Southern Leyte State University Sogod, Southern Leyte

Slr:

Herewith is our TECHNICAL PROPOSAL **for your office requirement:**

(INSTRUCTION TO BIDDER: <u>Check</u> the "Comply" box if bidder complies with the SLSU Specifications. A Technical Proposal containing unchecked "Comply" boxes would be automatically rated as "FAILED.")

ITEM	QTY	SLSU SPECIFICATIONS	BIDDER'S SPECIFICATIONS
		FURNITURE & FIXTURES	
1	6	 Glass Dry Erase Board with Marker Tray Magnetic White Size: 4x8 Height: 48 inches Length: 96 inches 	☐ Comply
		Width: 1/8 inches	
2	3	 Display and Storage Cabinet Steel Storage cabinet with Keyless electronic lock 4 adjustable shelves Height: 72 inches Width: 36 inches Depth: 18 inches 	☐ Comply
3	1	Office Sala Set / receiving Set Modular Polyester Sala Set Wood Frame and Metal Leg Sec A: 198 x 80 x 83 cm Sec B: 201 x 80 x 83 cm	☐ Comply

4		Class Cabinot (Office)	Comply
4	2	➤ Glass Cabinet (Office)	Comply
		Black Steel Clear View Storage Cabinet with Sliding Doors	
		4 adjustable shelves	
		Height: 72 inches Width: 36 inches	
		Depth: 18 inches	
		Depuil to inches	
5	1	Conference Room table and chairs (12-seater)	☐ Comply
		1 wooden round conference table	
		4200Wx1600Dx760H	
		12 Leather seats with arm rest	
		Seat Size: 29x25x47inches	
		, , , , , , , , , , , , , , , , , , , ,	
6	1	Unit Compact Kitchen Sink	☐ Comply
		1 pc 2-bowls stainless steel kitchen sink	
		70 L x 41 W x 20.7 H cm	
		1 stainless steel sink faucet	
		360 degree rotation	
		60 L x 10 W x 20 H cm	
		Installation Fee/ labor	
7	1		☐ Comply
/		Executive Office Desk	сопіріу
		1 wooden executive office desk	
		Height: 30 inches	
		Width: 59.5 inches	
		1 leather seat	
		Dimension: 29 inch W x 26 inch D x 48 inch H	
8	1		
		> Reception Desk	☐ Comply
		1 wooden reception desk	
		3.7 x 59 x 26.6 inches	
		ICT EQUIPMENT	
1	1	> Interactive Board	☐ Comply
'		Product Description ActivBoard 587 Pro	сопіріу
		•Resolution 14600 x 9200	
		Screen Surface Low glare melamine providing an efficient projection surface	
		Board Size 87" Diagonal	
		Overall Dimensions 2105mm x 1329mm	
		•Active Area Dimensions 1865mm x 1175mm	
		• Weight 40 kg	
		•Touch Response Rate 10ms	
		•User Input Cordless battery-free pen incorporating tip switch and side switch for full mouse functionality (ActivPen) and touch	
		•Connection To Computer USB 2.0, 1 x 3m USB 2.0 data cable required	
		- Connection to computer obs 2.0, 1 x 3111 obs 2.0 data casie required	
		•Connection To Peripherals 2 x USB ports on left hand side	
		•PC Requirement 2.0 GHz Intel Core 2 Duo or faster for HD-quality videos, 1 GB of	
		RAM is required to play HDquality videos, 1024 x 768 resolution, 1.5 GB of Free	
		Disk Space	
		'	

•Mac Requirement 2.0 GHz Intel Core 2 Duo, 512 MB of RAM, 1024 x 768 resolution, 3.0 GB of Free Disk Space •Linux Requirement 2.0 GHz Processor or faster for HD-quality videos, 1 GB of RAM is required to play HD-quality videos, 1024 x 768 resolution, 1.5 GB of Free Disk Space •Operating System Windows XP SP3 and above (XP/Vista/7); Mac OSX 10.4.11 -10.6.4 (Tiger/Leopard/Snow Leopard); Linux Ubuntu 9.10 or 10.04; Debian Lenny; Linex Colegios 2010; Linkat 3; ALT_Linux Branded Computers and Accessories Comply 2 99 PROCESSOR / CHIPSET CPU: Intel Core i5 (4th Gen) 4590 / 3.3 GHz Max Turbo Speed: 3.7 GHz Number of Cores: Quad-Core Chipset Type: Intel H81 Express Processor Main Features: Intel Turbo Boost Technology 2 Installed Size: 4 GB / 8 GB (max) Technology: DDR3 SDRAM - non-ECC Memory Speed: 1600 MHz Features: dual channel memory architecture Configuration Features: 1 x 4 GB Technology: DDR3 SDRAM Installed Size: 4 GB Data Integrity Check: non-ECC **MEMORY** Max Supported Size: 8 GB Form Factor: DIMM 240-pin Slots Qty: 2 Empty Slots: 1 HARD DRIVE Interface Type: SATA Spindle Speed: 7200 rpm Type: HDD Interface Class: Serial ATA Installed Qty: 1 Capacity: 500 GB STORAGE CONTROLLER Type: Serial ATA Installed Qty: 1 **OPTICAL STORAGE** Drive Type: DVD-Writer Type: DVD-Writer **PROCESSOR** Installed Qty: 1 Max Supported Qty: 1 Type: Core i5 Processor Number: i5-4590 Generation: 4 Manufacturer : Intel Clock Speed: 3.3 GHz

		NETWORKING	
		Data Link Protocol : Ethernet, Fast Ethernet, Gigabit Ethernet	
		Form Factor : integrated	
		Ethernet Controller(s): Realtek RTL8151GD	
		SYSTEM	
		Type : personal computer	
		Hard Drive Capacity : 500 GB	
		DIMENSIONS & WEIGHT	
		Width: 3.7 in	
		Depth : 12.3 in	
		Height: 11.4 in	
		GRAPHICS CONTROLLER	
		Form Factor: integrated	
		Graphics Processor: Intel HD Graphics 4600	
		Video Interfaces : DisplayPort, VGA CHASSIS	
		Form Factor : desktop slimline	
		Manufacturer Form Factor : small form factor	
		AUDIO OUTPUT	
		Form Factor : integrated	
		MAINBOARD	
		Chipset Type : Intel H81 Express	
		PHYSICAL CHARACTERISTICS	
		Form Factor : desktop slimline	
		Weight: 13.23 lbs	
		POWER	
		Type : power supply	
		OPERATING SYSTEM / SOFTWARE	
		OS Provided : Type : Microsoft Windows 7 Professional 64-bit Edition	
		OS Provided : Microsoft Windows 7 Professional 64-bit Edition + Windows 8.1 Pro	
		64-bit License - English / French	
		VIDEO OUTPUT	
		Graphics Processor: Intel HD Graphics 4600	
		Graphics Processor Series: Intel HD Graphics	
		Video Interfaces : DisplayPort, VGA	
3	25		☐ Comply
)	25	> Branded Desktop Computers for IOS Dev't.	☐ Comply
		Display ■ 21.5-inch (diagonal) LED-backlit display with IPS	
		technology	
		 1920-by-1080 resolution with support for millions of 	
		colors Processor	
		■ 2.8GHz	
		2.8GHz quad-core Intel Core i5 (Turbo Boost up to	
		3.3GHz) Memory	
		■ 8GB of 1867MHz LPDDR3 onboard memory	
		Configurable to 16GB	
		Storage¹ ■ 1.6GHz	
		1.66HZ 1TB (5400-rpm) hard drive	
		Configurable up to 1TB Fusion Drive or 256GB of flash	
		storage (SSD) ■ 2 8GHz	
		■ 2.8GHz 1TB (5400-rpm) hard drive	
		TID (5 100 Ipin) hard drive	

Configurable up to 2TB Fusion Drive or 256GB of flash storage (SSD)

Graphics

- 1.6GHz
 - Intel HD Graphics 6000
- 2.8GHz

Intel Iris Pro Graphics 6200

Video Support and Camera

- 1.6GHz
 - o FaceTime HD camera
 - Simultaneously supports full native resolution on the built-in display and up to 3840 by 2160 pixels on an external display
 - Support for extended desktop and video mirroring modes

■ 2.8GHz

- o FaceTime HD camera
- Simultaneously supports full native resolution on the built-in display and up to 4096 by 2304 pixels on an external display
- Support for extended desktop and video mirroring modes

Audio

- Stereo speakers
- Dual microphones
- 3.5 mm headphone jack
 - o Headphone/optical digital audio output (minijack)
 - Support for Apple iPhone headset with microphone

Connections and Expansion

- 3.5 mm headphone jack
- SDXC card slot
- Four USB 3 ports (compatible with USB 2)
- Two Thunderbolt 2 ports
 - Mini DisplayPort output
 - Support for HDMI, DVI, VGA, and dual-link DVI (adapters sold separately)
- 10/100/1000BASE-T Gigabit Ethernet (RJ-45 connector)
- Kensington lock slot

Input

Magic Keyboard

The redesigned Magic Keyboard comes standard. It's wireless and rechargeable (so you won't be replacing batteries), with an ultracompact, edge-to-edge design that wastes no surface space. It has an improved scissor mechanism, optimized key travel, and a lower profile that increase control and comfort. And it pairs immediately right out of the box.

Magic Mouse 2

The new design of Magic Mouse 2 lets it glide more smoothly across your desk. And since it supports Multi-Touch, you can use simple gestures on its surface to do things such as swipe between web pages and scroll through documents. So if you prefer to use a wireless mouse but want some of the benefits of Multi-Touch, Magic Mouse 2 is a great choice.

		 Magic Trackpad 2 	
		If you prefer using a trackpad, Magic Trackpad 2 gives	
		you the full range of Multi-Touch gestures and	
		introduces Force Touch to the desktop. Sensors	
		underneath the trackpad surface detect subtle	
		differences in the amount of pressure you apply,	
		bringing more functionality to your fingertips and	
		enabling a deeper connection to your content. This new	
		design, along with a lower profile, makes it even more	
		comfortable to use.	
		Wireless	
		■ Wi-Fi	
		802.11ac Wi-Fi wireless networking	
		IEEE 802.11a/b/g/n compatible	
		Bluetooth	
		Bluetooth 4.0 wireless technology	
		Size and Weight	
		■ 21.5-inch	
		Height: 17.7 inches (45.0 cm)	
		Width: 20.8 inches (52.8 cm)	
		Stand depth: 6.9 inches (17.5 cm)	
		Weight: 12.5 pounds (5.68 kg) ²	
		■ 21.5-inch with built-in VESA adapter	
		Height: 15.7 inches (37.9 cm)	
		Width: 20.8 inches (52.8 cm)	
		' '	
		Depth (including built-in VESA adapter): 2.6 inches (6.6	
		cm)	
		Electrical and Operating Requirements	
		Line voltage: 100–240V AC	
		■ Frequency: 50Hz to 60Hz, single phase	
		• Operating temperature: 50° to 95° F (10° to 35° C)	
		 Relative humidity: 5% to 95% noncondensing 	
		Operating altitude: tested up to 10,000 feet	Comply
4	5		
		> UPS	
		Battery Enclosure Type Internal	
		Subcategory UPS	
		POWER DEVICE	
		Voltage Required AC 120 V	
		• Input Voltage Range AC 95 - 142 V	
		 Power Output Connectors Details 6 x power NEMA 5-15 	
		• Output Voltage AC 120 V 50/60 Hz	
		Power Capacity 600 Watt / 1000 VA	
		• Surge Suppression yes	
		• Surge Energy Rating 445 Joules	
		• Power Provided 600 Watt	
		Circuit Protection circuit breaker	
		• Form Factor external	
		UPS Technology line interactive Voltage Provided AC 420 V	
		Voltage Provided AC 120 V Transport Provided 50/Co. U.S.	
		• Frequency Provided 50/60 Hz	
		 UPS Output Waveform stepped approximation to a sinewave 	

- Power Capacity (VA) 1000 VA
- Input Voltage Range (Adjustable) AC 87 152 V
- Input Connector Type power NEMA 5-15
- Input Connector Qty 1
- Output Connector Type power NEMA 5-15
- Output Connector Qty 6
- Surge Response Time o ns
- Power Device Features LCD display, audible alarm

BATTERY

- Technology Lead acid
- Run Time (Up To) 7.4 min

INTERFACE PROVIDED

- Qty 1
- Connector Type 9 pin D-Sub (DB-9)
- Type management (RS-232), management (USB)

MISCELLANEOUS

- Rack Mounting Kit included
- Equipment Protection Value 150000 US Dollars
- Features Audible alarm, LCD display
- Color gray
- Height (Rack Units) 2 m
- Color Category gray

ENVIRONMENTAL PARAMETERS

- Sound Emission 45 dBA
- Min Operating Temperature 32 °F
- Max Operating Temperature 104 °F
- Humidity Range Operating o 95%

CABLE DETAILS

- Type USB cable, power cable, serial cable
- Form Factor external
- Length 6 ft

POWER OUTPUT CONNECTORS DETAILS

- Connector Type power NEMA 5-15
- Connector Qty 6

DATALINE SURGE PROTECTION

- Type network
- Connector Type RJ-45

RUN TIME DETAILS

- Run Time (Up To) 7.4 min
- UPS
- Battery Technology lead acid

DIMENSIONS & WEIGHT

• Width 17 in

		D 11 0 1	_
		• Depth 18.2 in	
		• Height 3.5 in	
		• Weight 36.16 lbs	
		SERVICE & SUPPORT	
		• Type 2 years warranty	
		• SERVICE & SUPPORT DETAILS	
		• Full Contract Period 2 years	
		Type limited warranty	Comply
5	1	Type minica warranty	солгрту
		Vacuum Cleaner with polisher	
		• 6.5 peak HP motor provides powerful suction for heavy-duty	
		cleanup	
		• 20 ft. cord provides extra reach	
		Accessory storage space for all the included accessories and the	
		hose	
		• Air Watts: 286	
		Detachable hand held blower provides 180 mph wind for	
		removing debris from walkways, decks, yards, driveways, job	
		sites, tools, etc.	
		 Large built-in drain located at lowest point of drum for emptying 	
		of water	
		or water	Comply
6	1	CISCO Bundle for CCNA subject	
		,	
		• Cisco 1941/K9 Integrated Services Router	
		2 integrated 10/100/1000 Ethernet ports console and auxiliary	
		ports, up to 115.2 kbps each (RJ-45	
		2 enhanced High-Speed WAN Interface Card slots that can host Internal Services Module slot	
		WS-C2960-24TT-L	
		Cisco Catalyst 2960 Series switch	
		2x1GE uplink	
		24 Fast Ethernet port configurations	
		Advanced QoS, rate-limiting, Access Control Lists (ACLs), IPv6	
		management, IEEE 802.3af PoE with up to 15.4W per port for up	
		to 48 ports	
		• WRT120N	
		Linksys WRT120N Wireless-N Home Router	
		Ports: Internet, Ethernet (1-4), Power Reset, Wi-Fi Protected	
		Setup	
		• v.35 - DTE smart serial cable DTE serial cable	
		• v.35 - DCE smart serial cable DCE serial cable	
		• Cisco console cable RJ45 to DB9 Connectors	
		Open bay rack 2 posts floor mount 5ft	Comply
7	1 >	3D Printer	солгрту
'	-	•To maintain the garage-built feel and the handmade charms, I3	
		pro C is also a build-it-yourself kit, which provide you an	
		unforgettable step-by-step learning experience of 3D printer.	
		• The Geeetech i3 pro C is fast, easy to use, less costly, and great	
		for builds that don't require super high precision. The Replicator 1	

	1		1
		offers a layer height resolution of 0.1 mm - 0.3 mm, a positioning precision of 0.1-0.3mm on Z axis, and a maximum build envelope is 200 x200x180mm.	
		 Newly designed control system-GT2560 3D printer control 	
		board, a perfect combination of Arduino Mega2560+Ultimaker,	
		making 3D printing faster and easier.	
		making 30 printing faster and easier.	Comply
8	1		
		▶ Laser Jet	
		Print up to 10ppm Colour, 12ppm Monochrome	
		Print, Copy, Colour Scan functionality	
		• AirPrint Ready	
		• Wi-Fi enabled	
		Print ready	
		• Impressive colour with 1200 x 2400 dpi print resolution	
		• 525 MHz processor	
		• Eco-friendly with S-LED print engine technology and EA-Eco toner	
			Campulu.
		> 1 set Sound System Amplifier	Comply
9	1	MAIN UNIT SIZE (W X H X D)	
		455 x 165 x 330 mm	
		Main Hait Waink Caller	
		Main Unit Weight 6.3 Kg	
		Front Speaker Size (W X H X D) 510 X 773 X 458 Mm	
		Front Speaker Weight 33.0 Kg	
		Power Output 2400 W	
		Preset Eq Music/Football/Movie/Game/Drama/News	
		Bass Boost Function Mega Bass	
		CD TIMER (REC / PLAY / SLEEP) No/Yes/Yes	
		POWER SAVE MODE Yes	
		Network Connectivity	
		NFC: Yes	
		BLUETOOTH®: Yes	
		Speaker	
		Speaker System: 3way	
		Tweeter Unit: 2.5 Cm X 1 (Horn Type)	
		Mid Unit: 15 Cm X 1 (Paper)	
		Speaker Woofer Unit: 38 Cm X1(Mrc)	
		Detachable Grille: Black	
		Speaker Terminal (Front Speaker)	
		Direct Wire: Length Of Supplied Cable (Speaker)	
		2.5 M	
		Power	
		Power Consumption On: 375w	
		Power Consumption Standby: 0.5w	
		> Air con Split type	☐ Comply
10	3 units	• Nominal Size 1.5 HP	
.0	J 4	• Cooling Capacity 3,960-14,040 kJ/Hr	
		• Energy Efficiency Ratio 10.6-15.5 kJ/W-Hr	
		• Power Consumption 250-1,330 W	
		Tower Consumption 250-1,330 W	

	_		T
		•1.5HP	
		X-Power2 Advance Inverter Technology	
		Nano Filtration System	
		• Color: White	
		SKU CA684HAAA6HHTQANPH-13525847	
		Horsepower 1.5	
		Model FP-53CVUR013	
		Note: Installation included	
11	1 set	Ring Binder Machine	Comply
		Machine type - Comb type	
		Punching 80g/70g-A4/Sheets) 12/15	
		Binding 80g-A4/Sheets 220	
		Hole size mm 3X8	
		Hole qty pcs 21	
		Margin mm 3-6	Comply
13	1 unit		Comply
12	Tunic	> LCD Projector	
		• 5000 Lumens	
		• XGA (1024 x 768) Resolution	
		Digital DisplayPort & HDMI Connectivity	
		• Split Screen	
		• 10W Speaker Output	
		Direct On and Direct Off	
		Horizontal Keystone Slider Tool	
		DICOM Simulation Mode	
		• 1.6x Optical Zoom	
		Kensington Style Lock Provision	
		XGA, HDMI, USB Type B: 3-in-1 USB Display both for PC and	
		MAC, PDF viewer & PC-free presentations via USB memory	
		devices,	
		H & V keystone correction, Quick cornerstone correction, Split	
		screen, Quick start-up and Instant "Off" function.	
			☐ Comply
13	1 unit	> CCTV Package	
		1.3 Megapixel 8 Channel AHD Camera Kit, 720p or 1280×720	
		resolution, 8 Channel 720p Hybrid DVR with 8 x 720p (1.3MP)	
		Cameras / Cloud Peer to Peer' easy network connection software	
		/VGA & HDMI Output / Web and Smartphone remote viewing, use	
		analog CCTV Camera or as NVR for Ip Camera (onvif).	
		System	
		Main Processor - Embedded processor	
		Operating System Embedded LINUX	
		Video Input 8 channel, BNC	
		Standard NTSC(525Line, 60f/s), PAL(625Line, 50f/s)	
	1		

			Interface 1 HDMI, 1 VGA,	
			Resolution 1920×1080, 1280×1024, 1280×720, 1024×768,	
			800×600	
			Display Split 1/8	
			Privacy Masking 4 rectangular zones (each camera)	
			OSDCamera title, Time, Video loss, Camera lock, Motion	
			detection, Recording	
			Video/Audio Compression H.264 / G.711	
			Resolution	
			720P(1280×720/1280×600)/960H(960×576/960×480)/D1/4CIF	
			(704×576/704×480) / CIF(352×288/352×240) /	
			QCIF(176×144/176×120)	
			Main Stream: 720P/960H/D1/HD1/2CIF/CIF(1~25/30fps)	
			Extra Stream CIF/QCIF(1~25/30fps)	Comply
14	1 unit	► LED TV		Comply
14	Turne	➤ LED TV	Docklight	
			Backlight	
			LED	
			Screen Size (Inch)	
			40"	
			Resolution	
			1920 X 1080	
			Picture Engine	
			HyperReal	
			Dynamic Contrast Ratio	
			Mega Contrast	
			Dolby Digital Plus	
			Yes	
			Speaker Type	
			2CH(Down Firing w/Bass Reflex)	
			Digital Broadcasting	
			DVB-T/C	
			Power Supply (V)	
			AC100-240V 50/60Hz	
			Set Size without Stand (WxHxD)(mm)	
			922.7 x 530.7 x 72.0	
			Set Size with Stand (WxHxD)(mm)	
			922.7 x 582.3 x 226.5	
			Remote Controller Model	
			TM1240A	
			Power Cable	
			YES	
			Quick Install Guide	
			YES	
			Data Cable	
			YES	
			Stand Mount Kit	
			Stand Modiff Kit	

YES 2-2-2 warranty

NOTE:

Bidders must state here either "Comply" or "Not Comply" against each of the individual parameters of each Specification stating the corresponding performance parameter of the equipment offered. Statements of "Comply" or "Not Comply" must be supported by evidence in a Bidders Bid and cross-referenced to that evidence. Evidence shall be in the form of manufacturer's un-amended sales literature, unconditional statements of specification and compliance issued by the manufacturer, samples, independent test data etc., as appropriate. A statement that is not supported by evidence or is subsequently found to be contradicted by the evidence presented will render the Bid under evaluation liable for rejection. A statement either in the Bidders statement of compliance or the supporting evidence that is found to be false either during Bid evaluation, post-qualification or the execution of the Contract may be regarded as fraudulent and render the Bidder or supplier liable for prosecution subject to the provisions of ITB Clause Error! Reference source not found. and/or GCC Clause Error! Reference source not found.

Very truly yours,

Signature over printed name
Position
Company
Telephone Nos.
Date